





FEATURES & BENEFITS

Э

over galvanized steel to withstand bad weather.

Louvered construction with baked polyester finish



Raised coil to prevent debris blockage.



Proprietary aluminum blend coil with advanced corrosion resistance



4-screw louver panels, Corner-mounted controls and 45-degree offset valves for easy service.

Enhanced tube-and-fin coil design featuring high efficiency heat transfer technology

SPECIFICATIONS

- Factory installed high pressure switch
- Thread-on pressure switches for simple, quick replacement
- Charged for 15 feet of line set
- High-efficiency scroll compressor
- R410A refrigerant
- Heavy-duty compressor sound blanket for quiet operation
- Internally protected against high temperature motor overload conditions
- Factory installed filter drier

ир то 15 SEER / 8.5 HSPF CONDENSER HEAT PUMP SPLIT SYSTEM

MHP15*A

Affordable heating and cooling with up to 15 SEER & 8.5 HSPF efficiency in a durable Heat Pump System .

- Available in 1.5, 2, 2.5, 3, 3.5, 4, and 5 TON capacities
- 10-Year Parts Limited Warranty‡

‡Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty). Warranty must be registered online within 60 days of installation to qualify for 10-year coverage. Unregistered equipment defaults to 5-year coverage.

All units ETL and ETLC approved and AHRI Certified

